

LS9000 Series

Designed for steel and non-ferrous metal manufacturing. Provides high accuracy at a revolutionary price.

A breakthrough in electro-optics design enables Beta LaserMike's LaserSpeed® 9000 Series gauge to produce highly accurate, non-contact speed and length measurements, including zero speed and automatic direction detection, at a surprisingly low cost. To accomplish this, the LS9000 Series gauges use an enhanced version of autocorrelation, coupled with an Acusto-Optical modulator.

The LS9000 Series gauge is an industrial smart sensor that can be connected directly to a PLC or control computer. Speed, length, quality factor and gauge status information can be obtained via quadrature pulses, analog signals, serial communications and ethernet. With accuracy better than $\pm 0.05\%$, the LS9000 is the ideal gauge for replacing contact tachometers which are prone to measurement errors caused by slippage, dirt build-up, and day-to-day wear problems in the metal manufacturing industry.

LS9000: For normal environments (shown above right).

- Steel Slabs
- Plate Length
- Process Lines
- Cold Steel Strip
- Tube Length
- Painting Lines
- Steel Bar Length
- Bar Length
- Galvanizing Lines

LS9000E: For harsh, dry environments.
(A LS9000 gauge inside an environmental housing)

- Temper/Skin Pass Mills
- Foil Mills
- Slitter Lines
- Slabs
- Galvanizing Line
- Annealing Line
- Cold Steel Strip
- Painting Line
- Bar Mills
- Processing Lines
- Profile Mills
- Wire Rod Mills
- Tube Mills
- Plate Mills



LS9000X: For harsh, wet or hot environments.
(A LS9000 gauge inside a stainless steel housing)

- Hot Rolling Steel Mills
- Interstand Cold Rolling Steel Mills
- Heavy Steam Applications
- Extreme Hot and Hostile Environments



LaserSpeed®

Non-Contact Speed & Length Gauges

With Zero Speed and Automatic Direction Detection!



Benefits

- High accuracy and repeatability
- Rugged, sealed industrial packaging for use in industrial environments
- Non-contact length and speed measurement
 - No slippage
 - Non-marking
 - Not affected by material surface or color
- Measures zero speed
- Automatic direction detection
- Permanently calibrated
- Opto-isolated programmable pulse outputs
- Analog output for speed or status
- Compact, rugged industrial sensor operates on +24VDC



BETA LaserMike

Visit our website at:
www.betalasermike.com

Specifications

LS9000	-303	-306	-310	-315	-320	-325
Standoff Distance	300 mm (12 in.)	600 mm (24 in.)	1000 mm (39.4 in.)	1500 mm (59.1 in.)	2000 mm (78.1 in.)	2500 mm (98.4 in.)
Speed Range	0..+/-4000 m/min (0..+/-13100 ft/min)	0..+/-8000 m/min (0..+/-26200 ft/min)	0..+/-12000 m/min (0..+/-39400 ft/min)	0..+/-19000 m/min (0..+/-62400 ft/min)	0..+/-20000m/min (0..+/-65600ft/min)	0..+/-20000m/min (0..+/-65600ft/min)
Measurement Depth of Field	35 mm (1.4 in.)	50 mm (2.0 in.)	100 mm (4.0 in.)	200 mm (8.0 in.)	200 mm (8.0 in.)	200 mm (8.0 in.)

LS9000 General Specifications

Accuracy

Depth of Field <75mm	<+/-0.05% of reading
Depth of Field >75mm	<+/-0.1% of reading

Repeatability

+/-0.02%

Measurement Rate

>100,000/s

Acceleration Rate

>500 m/s²

Starting/ Ending Length Correction

- Yes

Serial I/O

Data Available	- RS-232 / RS-422 - Speed, Length - Quality Factor, Status
Baud Rate	- 115K, 230K - 19.2K, 38.4K, 57.6K

Ethernet -Optional

- 10/100, UDP,TCP
- Speed, Length
- Quality Factor, Status

Status via Serial I/O or Optional Ethernet

- Laser at Temperature
- Laser Interlock
- Shutter Position
- Valid Measurements
- Material Present
- System Ready

Quadrature Pulse

Output 1	- Opto isolated - Scaleable pulse amplitude (5-24V) - Selectable pulses/unit - 250 KHz max pulse rate
Output 2	- RS-422 Drivers - Selectable pulses/unit - 5 MHz max pulse rate

Gauge Power

- 24VDC (+/-4 VDC) @ 2.0 Amp

Gauge Temperature

- 5 to 45°C (41 to 113°F)

Specifications are subject to change without notice.

LS9000

Gauge Size

-303, -306, -310	203 X 159 X 95.2 mm (8.0 X 6.3X 3.75 in.)
-315, -320, -325	228.6 X 159 X 95.2 mm (9 X 6.3 X 3.75 in.)

Gauge Weight

-303, -306, -310	3.4 kg (7.5 lbs)
-315, -320, -325	3.7 kg (8.3 lbs)

Water Cooling

1.0 to 3.8 l/min, Typical 1.5 l/min (0.4 gpm)

Relative Humidity

Non-condensing

Degree of Protection

IP67

LS9000E

Gauge Size

-303, -306, -310	362 X 229 X 154 mm (14.25 X 9 X 6 in.)
-315, -320, -325	362 X 229 X 154 mm (14.25 X 9 X 6 in.)

Gauge Weight

-303, -306, -310	18 kg (40 lbs)
-315, -320, -325	Varies depending on Air Wipe/Air Purge

Environment Temp.

-10 to 150°C (14 to 302°F)

Water Cooling

1.0 to 3.8 l/min (0.26 – 1gpm)

Compressed Air

Instrument grade	50 l/min (1.8 cfm) Typical
Air wipe	6.2 – 8.3 Bar, 1200 l/min (90 -120psi, 45 scfm)
Air Purge	

Relative Humidity

Non-condensing

Degree of Protection

IP67

LS9000X

Gauge Size

-303, -306, -310	508 X 327 X 186 mm (20 X12.88 X 7.32 in.)
-315, -320, -325	508 X 327 X 186 mm (20 X12.88 X 7.32 in.)

Gauge Weight

-303, -306, -310	24.9 kg (55 lbs)
-315, -320, -325	24.9 kg (55 lbs)

Environment Temp.

-10 to 200°C (14 to 392°F)

Water Cooling

1.0 to 3.8 l/min (0.26 – 1gpm)

Compressed Air

Instrument grade	50 l/min (1.8 cfm) Typical
Air wipe	6.2 – 8.3 Bar, 1200 l/min (90 -120psi, 45 scfm)
Air Purge	

Relative Humidity

Non-condensing

Degree of Protection

IP67

This unit is a class IIIB laser product and Complies with EN60825-1:2001. Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated July 26, 2001.



The following safety features required to comply with the Bureau of Radiological Health Class IIIB laser requirements are included:

- Key-operated power switch on optional controller
- Laser indicator light on supply and laser
- Delayed laser startup-laser indicator light on prior to laser radiation
- Laser beam blocking device
- Interlock capability for remote shut-off

BETA LaserMike

Beta LaserMike USA

8001 Technology Blvd.
Dayton, OH 45424 USA
Ph: +1 937 233 9935
Fax: +1 937 233 7284

Beta LaserMike Europe

Unit 3, First Avenue
Globe Park, Marlow
Buckinghamshire, SL7 1YA
United Kingdom
Ph: +44 1628 401510
Fax: +44 1628 401511

Beta LaserMike Asia

SHANGHAI
BLOCK AUTOMATION.,LTD
Shanghai 200270, China
Ph: +86 21 66119899
Fax: +86 21 66119895

Visit our website at : www.betalasermike.com